ĽB-LINK®



Features

Plug and play without setup

In any location, power can quickly convert 4G network to WI-FI network, no setup, quickly realize the sharing of multiple people online


Dual network access

Support 4G network as the backup line of wired broadband, in the case of abnormal wired broadband, automatic switch, never drop the line

150M high bandwidth

The 4G network supports CAT4 standard, the maximum download rate is up to 150M, and the Internet is smooth and slow





Specifications

Chip	MT7628DAN
Protocol standard	2.4G Wireless: IEEE802.11b/g/n
Ethernet	IEEE802.3u
3G/4G Band	4G Band: FDD-LTE: B1/B3/B5/B7/B8/B20/B28, TDD-LTE: B38/B40/B41 3G Band: WCDMA: B1/B5/B8
Transmission rate	300Mbps
Frequency range	2.4 to 2.4835GHz
Working channel	1~13CH
Transmit power	20dBm(maximum)
Interface	2 LAN+ 1 WAN
Indicators	Network indicator blue + System indicator red
Antennas	Two external 5dBi WIFI antennas, Two external 3dBi LTE antennas
Input power	DC 12V/1A power supply
Security feature	WPA/WPA2-PSK
Operating environment	Operating temperature: 0°C~40°C (32°F~104°F) Storage temperature: -40°C~70°C (-40°F~158°F) Operating humidity: 10%-90% RH Without condensation Storage humidity: 5%-90% RH No condensation
Operating system	Microsoft Internet Explorer 10 or later

LB-LINK is the registered trademark of Shenzhen BILIAN Electronic CO.,Ltd. All the products and product names mentioned here are the trademarks or registered trademarks of their respective holders, Specifications are subject to change without notice. Copyright © 2012 LB-LINK All Rights Reserved. Add: Room 501, Building 3, No. 32 Dafu Road, Zhangge Community, Fucheng Street, Longhua District, Shenzhen City. Any questions please contact: info@lb-link.cn

